

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended) A radio communication system comprising first and second radio communication apparatuses which can communicate with each other by radio,

wherein said first radio communication apparatus comprises:

a propagation path environment estimator which outputs, as propagation path environment information, a result of estimation of an environment of a propagation path to said second radio communication apparatus on the basis of a signal from said second radio communication apparatus;

a propagation path quality estimator which outputs, as propagation path quality information, a result of estimation of quality of the propagation path to said second radio communication apparatus on the basis of the signal from said second radio communication apparatus;

an error detector which detects an error in the signal from said second radio communication apparatus and outputs the error as an error detection result; and

transmitting means for transmitting the propagation path environment information, ~~and~~ propagation path quality information, and error detection result together with a data signal to said second radio communication apparatus,

~~and~~-wherein said second radio communication apparatus comprises:

a transmission mode selector which includes a plurality of tables in which a plurality of transmission modes each having a threshold value corresponding to a value of the propagation path quality information are registered, selects one of said plurality of tables in accordance with the propagation path environment information, and selects, as a mode for transmission to said first radio communication apparatus, one of the transmission modes registered in the selected table in accordance with the propagation path quality information,

wherein said transmission mode selector of said second radio communication apparatus rewrites, in accordance with the error detection result, a threshold value registered in the table to correspond to the selected transmission mode.

2. (canceled).

3. (currently amended): A radio communication system according to claim 1, wherein ~~the~~a path count is used as the propagation path environment information.

4. (currently amended): A radio communication system according to claim 3, wherein ~~a~~the plurality of tables correspond to path counts P1, P2,..., PR (P1, P2,..., PR are natural numbers and satisfy  $P1 < P2 < \dots < PR$ ).

5. (Original) A radio communication system according to claim 1, wherein a maximum Doppler frequency is used as the propagation path environment information.

6. (currently amended) A radio communication system according to claim 5, wherein ~~a~~the plurality of tables correspond to maximum Doppler frequencies  $f_0, f_1, \dots, f_{R-1}$  ( $f_0 < f_1 < \dots < f_{R-1}$ ), and, with respect to a threshold value  $x_i$  ( $x_i$  is an arbitrary number which satisfies  $f_i < x_i < f_{i+1}$ , and  $i$  is an integer from 0 to  $R - 2$ ), if a maximum Doppler frequency  $f_d$  is  $x_{j-1} < f_d \leq x_j$  ( $j$  is an integer from 1 to  $R - 2$ ),  $f_j$  is selected as the maximum Doppler frequency, if  $f_d \leq x_0$ ,  $f_0$  is selected as the maximum Doppler frequency, and if  $f_d > x_{R-2}$ ,  $f_{R-1}$  is selected as the maximum Doppler frequency.

7. (Original) A radio communication system according to claim 1, wherein a delay dispersion is used as the propagation path environment information.

8. (currently amended) A radio communication system according to claim 7, wherein ~~a~~the plurality of tables correspond to delay dispersions  $\sigma_0, \sigma_P, \dots, \sigma_{R-1}$  ( $\sigma_0 < \sigma_1 < \dots < \sigma_{R-1}$ ), and, with respect to a threshold value  $x_i$  ( $x_i$  is an arbitrary value which satisfies  $\sigma_i < x_i < \sigma_{i+1}$ , and  $i$  is an integer from 0 to  $R - 2$ ), if a delay dispersion  $\sigma$  is  $x_{j-1} < \sigma \leq x_j$  ( $j$  is an integer from 1 to  $R - 2$ ),  $\sigma_j$  is selected as the delay dispersion, if  $\sigma \leq x_0$ ,  $\sigma_0$  is selected as the delay dispersion, and if  $\sigma > x_{R-2}$ ,  $\sigma_{R-1}$  is selected as the delay dispersion.

9. (currently amended) A radio communication system according to claim 1, wherein ~~a~~the plurality of selection tables correspond to combinations of path counts  $P_1, P_2, \dots, P_J$  ( $P_1, P_2, \dots, P_J$  are natural numbers not more than  $R$  and satisfy  $P_1 < P_2 < \dots < P_J$ ) and maximum Doppler frequencies  $f_0, f_1, \dots, f_{K-1}$  ( $K$  is a natural number not more than  $R$  and satisfies  $J \times K = R$ ).

10. (currently amended) A radio communication apparatus according to claim 1, wherein ~~a~~the plurality of tables correspond to combinations of path counts  $P_1, P_2, \dots, P_J$  ( $P_1, P_2, \dots, P_J$  are natural numbers and satisfy  $P_1 < P_2 < \dots < P_J$ ) and delay dispersions  $\sigma_0, \sigma_P, \dots, \sigma_{K-1}$  ( $L$  is a natural number not more than  $R$  and  $J \times L = R$ ) (if the path count is 1, the delay dispersion is not used as the propagation path environment information).

11. (currently amended) A radio communication system according to claim 1, wherein ~~a~~the plurality of tables correspond to combinations of maximum Doppler frequencies  $f_0$  to  $f_{K-1}$  and delay dispersions  $\sigma_0$  to  $\sigma_{L-1}$  ( $L$  is a natural number not more than  $R$  and  $K \times L = R$ ).

12. (currently amended) A radio communication system according to claim 1, wherein ~~a~~the plurality of tables correspond to combinations of path counts  $P_1, P_2, \dots, P_J$ , maximum Doppler frequencies  $f_0$  to  $f_{K-1}$ , and delay dispersions  $\sigma_0$  to  $\sigma_{L-1}$  ( $J, K, L$ , and  $R$  are

natural numbers which satisfy  $J \times K \times L = R$ ) (if the path count is 1, the delay dispersion is not used as the propagation path environment information).

13. (Original) A radio communication system according to claim 1, wherein a signal-to-interference ratio is used as the propagation path quality information.

14. (Original) A radio communication system according to claim 1, wherein a signal-to-noise ratio is used as the propagation path quality information.

15. (Original) A radio communication system according to claim 2, wherein a modulation technique is used as a parameter of a transmission mode.

16. (Original) A radio communication system according to claim 2, wherein an encoding ratio is used as a parameter of a transmission mode.

17. (previously presented) A radio communication system according to claim 2, wherein a transmission power is used as a parameter of a transmission mode.

18. (canceled).

19. (currently amended) A transmission mode selection method performed in a radio communication system comprising first and second radio communication apparatuses which can communicate with each other by radio, wherein the method comprises:

~~the first step, performed estimating, by the first radio communication apparatus, of~~  
~~estimating~~ propagation path environment information indicating an environment of a propagation path to the second radio communication apparatus on the basis of a signal from the second radio communication apparatus;

~~the second step, performed estimating, by the first radio communication apparatus, of~~  
~~estimating~~ propagation path quality information indicating quality of the propagation path to the second radio communication apparatus on the basis of the signal from the second radio communication apparatus;

~~the third step, performed obtaining, by the first radio communication apparatus, of~~  
~~obtaining~~ an error detection result indicating an error in the signal from the second radio communication apparatus;

~~the fourth step, performed transmitting, by the first radio communication apparatus, of~~  
~~transmitting~~ the propagation path environment information, propagation path quality information, and error detection result together with a data signal to the second radio communication apparatus; and

~~the fifth step, performed selecting,~~ by the second radio communication apparatus, of  
selecting, in accordance with the propagation path environment information, one of a plurality of  
tables in each of which a plurality of transmission modes each having a threshold value  
corresponding to a value of the propagation path quality information are registered, selecting, as  
a mode for transmission to the first radio communication apparatus, one of the transmission  
modes registered in the selected table in accordance with the propagation path quality  
information, and rewriting, in accordance with the error detection result, a threshold value  
registered in the table to correspond to the selected transmission mode.